

 **COMPACTNESS AT ITS BEST**



CPBATTERY CP160B

Battery Operated Portable X-Ray Generator



TELEDYNE ICM
Everywhereyoulook™

Part of the Teledyne Imaging Group

All the power you need and more



LIGHTWEIGHT



BATTERY OPERATED




SMALL FOCAL SPOT



DR-READY



UP TO 160 KV



ROTATING TANK





FEATURES

	Unit	CP160B
Beam	-	Directional
Power supply	-	Battery
Output voltage range	kV	40 to 160
Tube current range	mA	0.1 to 0.5
Tube current at full output	mA	0.5
Maximum power at the anode	W	80
Constant power mode	-	Yes
Working cycle at 30°C (*)	%	/
Steel penetration (**)	mm/in	21 / 0.8
Weight (excluding hand rings)	Kg/lbs	9.2 / 20.3
Overall dimensions	mm/in	Ø 124 x 520 / 4.9 x 20.5
Leakage dose at 1 m at full output	mSv/h	< 2.0
Optical focal spot according to EN 12543	mm/in	0.8 x 0.7 / 0.03 x 0.03
Maximum useful angle	°	60 x 60
Inherent filtration	mm/in	Equiv. 3.5 / 0.1 (Al)
Waterproof level	-	IP54
Operating temperature	°C/°F	-25 to +50 / -13 to +140
Storage temperature	°C/°F	-40 to +80 / -40 to +176
Guard rings	-	/

(*) Open air - airstream 5m/sec.

(**) 400 mm FFD, 1 min, AA400, D=2 for CPB

DRAWINGS



ACCESSORIES



RUGGEDIZED
STRUCTURE



ADJUSTABLE
COLLIMATOR



CARBON
TRIPOD



FAST
BATTERY
CHARGER



TRIGGER



EXTERNAL
POWER
SUPPLY

All specifications are non contractual and subject to change without prior notice.

TELEDYNE ICM

Zoning Les Plennes / Rue Du Progrès 3 / B-4821 Andrimont (Dison) - Belgium

+32 (0)87 44 01 50 / icm.sales@teledyne.com



TELEDYNE ICM
Everywhereyoulook™

Part of the Teledyne Imaging Group