



BEST WEIGHT TO POWER RATIO IN THE WORLD



CP SERIES CP200DS

Small Focal Spot Constant Potential Portable X-Ray Generators



TELEDYNE ICM
Everywhere you look™

Part of the Teledyne Imaging Group

Your inspection becomes a walk in the park



LIGHTWEIGHT



100% DUTY CYCLE



CONSTANT
POTENTIAL



METAL CERAMIC
TUBE



RUGGEDIZED



WIDE INPUT
POWER RANGE

FEATURES

	Unit	SITEX CP200DS
Beam	-	Directional
Power supply	-	Mains
Output voltage range	kV	10 to 200
Tube current range	mA	0.5 to 10
Tube current at full output	mA	3.7
Maximum power at the anode	W	750
Constant power mode	-	Yes
Working cycle at 30°C (*)	%	100
Steel penetration (**)	mm/in	40 / 1.57
Weight	Kg/lbs	15.9 / 35.05
Overall dimensions (without guard rings)	mm/in	Ø 140 x 705 / 5.51 x 27.75
Leakage dose at 1 m at full output	mSv/h	< 2.0
Optical focal spot according to EN 12543	mm	1
Maximum useful angle	°	60° x 40°
Inherent filtration	mm	0.8 mm Be
Protection class	-	IP65
Operating temperature	°C/F°	-30 to +60 / -22 to +140
Storage temperature	°C/F°	-40 to +70 / -40 to +158

(*) Open air - airstream 5m/sec.


(**) 700 mm FFD, 10 min., AA400, D=2 for CPD

POWERBOX

	Unit	POWERBOX
Adjustable pre-warming time	sec	5 to 255
Pilote light indicator	-	3
Independent START and STOP	-	Yes
Two-position safety key rotary switch	-	X-ray ON / STANDBY
Preheating is function of selected kVs (kV max by default)	-	Automatic
Exposure time calculator	-	Optional
Programmable safety interlocks	-	3
Clear indication of the precise carousel system position	-	Yes
Type of power supply	-	Mains, Power generator, Battery (option)
Supply voltage range	VAC	From 90 to 264
Supply frequency range	Hz	From 45 to 66
Input power factor when at full output	%	99
Input current at full power, 230 VAC	A	6.0
Storage temperature	°C/F°	-40 to +70 / -40 to 158
Operating temperature	°C/F°	-30 to +55 / -22 to 131
Protection class	-	IP65
Weight	Kg/lbs	7.9 / 17.4

Communication: Wi-Fi (works with Sherlock NDT)


CP SERIES BUILD-IN CAROUSEL | 5 OUTPUT POSITIONS



ACCESSORIES

Quadripod	Transport case
Holding bars	Flashing light
Tripod	Diaphragms
Pipe slider	Reinforced cable
Alucase	Tripod flashing light
Battery converter	

DRAWINGS



All specifications are non contractual and subject to change without prior notice.

TELEDYNE ICM

Zoning Les Plennes / Rue du Progrès 3 / B-4821 Andrimont (Dison) - Belgium

+32 (0)87 44 01 50 / icm.sales@teledyne.com



TELEDYNE ICM
Everywhere you look™

Part of the Teledyne Imaging Group